



FRC / D-SUB (M / F) CONNECTOR TO WIRE



Schematic



Schematic

VOLTAGE RATING	100VDC		
CURRENT RATING	INPUT	500mA	
	OUTPUT	500mA	
OPERATING AMBIENT	0-55°C, 85% RH		
STORAGE AMBIENT	-20°C to 85°C		
TERMINATIONS	INPUT SIDE	FRC / D-SUB	
	OUTPUT SIDE	Screw type, suitable for 2.5mm sq. wire	
MOUNTING	35 mm DIN rail		

ORDERING INFORMATION	ORDER CODE	No. OF CHANNELS	DIMENSIONS W x H x D (mm)	WEIGHT (MAX)	ORDER CODE	MALE	FEMALE	No. OF CHANNELS	DIMENSIONS W x H x D (mm)	WEIGHT (MAX)
	AS581	10	46 x 80 x 70	75 grams		AS591-M	AS591-F	9	46 x 80 x 70	80 grams
	AS582	14	46 x 80 x 70	80 grams		AS592-M	AS592-F	15	68 x 80 x 70	100 grams
	AS583	16	68 x 80 x 70	100 grams		AS593-M	AS593-F	25	91 x 80 x 70	150 grams
	AS584	20	68 x 80 x 70	120 grams		AS594-M	AS594-F	37	113 x 80 x 70	200 grams
	AS585	26	91 x 80 x 70	140 grams		AS595-M	AS595-F	50	137 x 80 x 70	220 grams
	AS586	34	113 x 80 x 70	180 grams						
	AS587	40	113 x 80 x 70	185 grams						
	AS588	50	137 x 80 x 70	230 grams						
	AS589	60	180 x 80 x 70	260 grams						
AS590	64	180 x 80 x 70	270 grams							