


## DC - DC CONVERTER 24W



All dimensions in mm

<b>FEATURES</b>	<ul style="list-style-type: none"> <li>DC Input</li> <li>Built In Transient protector &amp; EMI filter</li> <li>Protection against short circuit, overload &amp; overvoltage</li> <li>Low ripple &amp; noise</li> <li>Cooling by free air convection</li> </ul>	<ul style="list-style-type: none"> <li>Power OK indication, terminations, output set control &amp; rating details on front</li> <li>100% full load burn in tested</li> <li>Low cost</li> <li>High reliability</li> <li>Compact</li> </ul>			
<b>ISOLATION</b>	Input – Output : 1.5KVAC, 1 minute Input – Earth : 1.5KVAC, 1 minute Output – Earth : 0.5KVAC, 1 minute				
<b>EFFICIENCY</b>	70 ~ 75%				
<b>O/P VOLTAGE ADJUSTMENT</b>	+/- 10% of nominal output voltage				
<b>OVERLOAD PROTECTION</b>	105% ~ 130% of rated load				
<b>LINE &amp; LOAD REGULATION</b>	Better than 0.5%				
<b>OPERATING AMBIENT</b>	0 ~ 50°C, 95% RH				
<b>STORAGE AMBIENT</b>	-20°C to 85°C				
<b>SAFETY STANDARD</b>	Design refers to EN60950-1				
<b>EMC STANDARD</b>	Design refers to EN55022, EN55024				
<b>TERMINATIONS</b>	Screw type, for 2.5mm sq. wire				
<b>MOUNTING</b>	35 mm DIN rail				
<b>WEIGHT</b>	240 grams				
<b>ORDERING INFORMATION</b>		<b>NOMINAL INPUT : 24VDC</b>	<b>OUTPUT</b>	<b>RIPPLE &amp; NOISE</b>	<b>OVERVOLTAGE PROTECTION</b>
	<b>INPUT RANGE</b>	18 ~ 36VDC			
	<b>I/P CURRENT (max)</b>	1.5A @24VDC			
	<b>ORDER CODE</b>	G34-24-05	5V : 2.5A	< 100mV	< 7V
		G34-24-12	12V : 2A	< 120mV	< 16V
		G34-24-24	24V : 1A	< 240mV	< 30V

Note : 1. All parameters measured at nominal input, rated load and 25°C of ambient temperature unless otherwise specified.  
 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 100uf parallel capacitor.  
 3. The power supply is intended to be installed as a component inside the enclosure of final equipment. The final equipment must be re-confirmed that it still meets the EMC directives.  
 4. These units are designed for mounting on horizontal DIN rail. Ensure clearance of minimum 35mm from adjacent components for proper ventilation.